

Product data sheet

Characteristics

9070TF200D5

Transformer, Type TF, industrial control, 200 VA,
120/240 VAC primary / 12/24 VDC second, 1
phase, 50/60 Hz, 80 °C rise



Product availability: Stock - Normally stocked in distribution facility

Price*: 293.00 USD

Main

Product or Component Type	Industrial Control Transformer
Rated power in VA	200 VA
Primary Voltage	120 x 240 V
Secondary Voltage	12/24 V
Range of Product	TF

Complementary

Phase	1 phase
Rated power in VA	200 VA
Primary voltage	120 x 240 V 12/24 V
Fuse type	10.3 x 38 mm CC top
Temperature rise	80 °C
Electrical Connection	Screw clamp terminals
Maximum Height	4.5 In (114.30 mm)
Maximum Width	3.75 In (95.25 mm)
Maximum Depth	3.59 In (91.19 mm)
Material	Copper winding
Product Compatibility	FSC1

Environment

Product Certifications	CSA UL Listed
NEMA Degree of Protection	Not rated (open device)
Insulation temperature	266 °F (130 °C)

Ordering and shipping details

Category	16202 - 9070 TF (NOT T) 50-200VA
Discount Schedule	CP8
GTIN	00785901414308
Nbr. of units in pkg.	1
Package weight(Lbs)	6.21 Lb(US) (2.82 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	6.60 In (16.764 cm)
Package 1 width	6.00 In (15.240 cm)
Package 1 Length	8.00 In (20.320 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**