

# Product data sheet

## Characteristics

# 9070TF250D5

Transformer, Type TF, industrial control, 250 VA,  
600 VAC primary /120 VAC secondary, 1 phase,  
50/60 Hz, 80 °C rise



Product availability: Stock - Normally stocked in distribution facility

Price\*: 687.00 USD

### Main

Rated power in VA	250 VA
Primary Voltage	600 V 575 V 550 V
Secondary Voltage	110/115/120 V

### Complementary

Fuse type	0.41 x 1.50 in CC top
Temperature rise	80 °C
Maximum Height	4.55 In (115.57 mm)
Maximum Width	3.75 In (95.25 mm)
Maximum Depth	5.25 In (133.35 mm)
Material	Copper winding

### Environment

Product Certifications	CE CSA file LR37055 guide 184-N-90 UL listed file E61239
Insulation temperature	266 °F (130 °C)

### Ordering and shipping details

Category	16207 - 9070 TF (NOT T) MTO
Discount Schedule	CP8
GTIN	00785901307068
Nbr. of units in pkg.	1
Package weight(Lbs)	7.70 Lb(US) (3.493 kg)
Returnability	No
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.50 In (16.51 cm)
Package 1 width	6.80 In (17.272 cm)
Package 1 Length	7.60 In (19.304 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**