

Product data sheet

Characteristics

9070TF350D20

Transformer, Type TF, industrial control, 350 VA, 208/230/460 VAC primary / 115 VAC sec, 1 phase, 50/60 Hz, 80 °C rise



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 585.00 USD

Main

Product or Component Type	Industrial Control Transformer
Rated power in VA	350 VA
Primary Voltage	208/230/460 V
Secondary Voltage	115 V
Range of Product	TF

Complementary

Phase	1 phase
Rated power in VA	350 VA UL 350 VA CSA 350 VA NOM 250 VA
Primary voltage	208/230/460 V 115 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	80 °C
Electrical Connection	Screw clamp terminals
Maximum Height	5.13 In (130.30 mm)
Maximum Width	4.5 In (114.30 mm)
Maximum Depth	5.49 In (139.45 mm)
Material	Copper winding
Product Compatibility	FSC2

Environment

Product Certifications	UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA Degree of Protection	Not rated (open device)
Insulation temperature	266 °F (130 °C)

Ordering and shipping details

Category	16207 - 9070 TF (NOT T) MTO
Discount Schedule	CP8
GTIN	00785901398035
Nbr. of units in pkg.	1
Package weight(Lbs)	11.90 Lb(US) (5.398 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.00 In (15.24 cm)
Package 1 width	7.50 In (19.05 cm)
Package 1 Length	6.50 In (16.51 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**