

# Product data sheet

## Characteristics

# 9070TF500D50

Transformer, Type TF, industrial control, 500 VA,  
208/360/416/520 VAC pri / 85/104/115 VAC sec,  
1 phase, 50/60 Hz, 115°C



Product availability: Stock - Normally stocked in distribution facility

Price\*: 753.00 USD



### Main

Product or Component Type	Industrial Control Transformer
Rated power in VA	500 VA
Primary Voltage	220/380/440/550 V 240/416/480/600 V 208/360/416/520 V 230/400/460/575 V
Secondary Voltage	85/104/115 V 90/110/120 V 99/120/130 V 95/115/125 V
Range of Product	TF

### Complementary

Phase	1 phase
Rated power in VA	500 VA UL 500 VA CSA 500 VA NOM 300 VA
Primary voltage	208/360/416/520 V 85/104/115 V 220/380/440/550 V 90/110/120 V 230/400/460/575 V 95/115/125 V 240/416/480/600 V 99/120/130 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	115 °C
Electrical Connection	Screw clamp terminals
Maximum Height	5.81 In (147.57 mm)
Maximum Width	5.25 In (133.35 mm)
Maximum Depth	5.61 In (142.49 mm)
Material	Copper winding
Product Compatibility	FSC23

## Environment

Product Certifications	UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA Degree of Protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

## Ordering and shipping details

Category	16203 - 9070 TF (NOT T) 250-1000VA
Discount Schedule	CP8
GTIN	00785901563624
Nbr. of units in pkg.	1
Package weight(Lbs)	17.20 Lb(US) (7.802 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.00 In (17.78 cm)
Package 1 width	8.20 In (20.828 cm)
Package 1 Length	8.60 In (21.844 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**