

Product data sheet

Characteristics

9070TF750D50

Transformer, Type TF, industrial control, 750 VA,
240/416/480/600 VAC pri / 99/120/130 VAC sec,
1 phase, 50/60 Hz, 115°C



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 858.00 USD

Main

Product or Component Type	Industrial Control Transformer
Rated power in VA	750 VA
Primary Voltage	240/416/480/600 V 220/380/440/550 V 208/360/416/520 V 230/400/460/575 V
Secondary Voltage	99/120/130 V 95/115/125 V 85/104/115 V 90/110/120 V
Range of Product	TF

Complementary

Phase	1 phase
Rated power in VA	750 VA UL 750 VA CSA 750 VA NOM 500 VA
Primary voltage	208/360/416/520 V 85/104/115 V 220/380/440/550 V 90/110/120 V 230/400/460/575 V 95/115/125 V 240/416/480/600 V 99/120/130 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	115 °C
Electrical Connection	Screw clamp terminals
Maximum Height	5.8 In (147.32 mm)
Maximum Width	5.25 In (133.35 mm)
Maximum Depth	6.3 In (160.02 mm)
Material	Copper winding
Product Compatibility	FSC23

Environment

Product Certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239
NEMA Degree of Protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

Ordering and shipping details

Category	16207 - 9070 TF (NOT T) MTO
Discount Schedule	CP8
GTIN	00785901069232
Nbr. of units in pkg.	1
Package weight(Lbs)	1 Lb(US) (0.45 kg)

Returnability	No
Country of origin	US

Packing Units

Package 1 Height	6.50 In (16.510 cm)
Package 1 width	8.50 In (21.590 cm)
Package 1 Length	8.00 In (20.320 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	-----------------------