

# Product data sheet

## Characteristics


# 9422ATCN302

Operating mechanism, flange mounted, variable depth, 30A, 600 V, no fuse, switch mechanism, 6 inch handle, NEMA 4X



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 686.30 USD



### Main

Range of product	9422T
Product or component type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch

### Complementary

Product mounting	Flange rod variable depth
Line Rated Current	30 A
Maximum Horse Power Rating	7.5 Hp 200 V AC 7.5 Hp 230 V AC 15 Hp 460 V AC 20 Hp 575 V AC 5 Hp 250 V DC
Provided equipment	6 in handle included NEMA 4/4X enclosures Stainless Steel

### Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

### Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901326526
Nbr. of units in pkg.	1
Package weight(Lbs)	13.96 Lb(US) (6.331 kg)
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.00 In (5.08 cm)
Package 1 width	4.00 In (10.16 cm)
Package 1 Length	9.00 In (22.86 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**