

# Product data sheet

## Characteristics

# 9422ATDN601

Operating mechanism, flange mounted, variable depth, 60A, 600 V, no fuse, switch mechanism, 6 inch handle, NEMA 4



Product availability: Stock - Normally stocked in distribution facility

Price\*: 618.20 USD



### Main

Range of product	9422T
Product or component type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch

### Complementary

Product mounting	Flange rod variable depth
Line Rated Current	60 A
Maximum Horse Power Rating	15 Hp 200 V AC 15 Hp 230 V AC 30 Hp 460 V AC 50 Hp 575 V AC 10 Hp 250 V DC
Provided equipment	6 in handle included NEMA 1/3/3R/4 enclosures sheet steel

### Environment

Product certifications	CSA UL Recognized
------------------------	----------------------

### Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901872177
Nbr. of units in pkg.	1
Package weight(Lbs)	8.30 Lb(US) (3.765 kg)
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.10 In (18.034 cm)
Package 1 width	11.30 In (28.702 cm)
Package 1 Length	16.00 In (40.64 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**