

# Product data sheet

## Characteristics

# 9422ATF12

Operating mechanism, flange mounted, variable depth, 200A, 600V, fuseholder, switch mechanism, 6 inch handle, NEMA 4



Product availability: Stock - Normally stocked in distribution facility

Price\*: 1794.70 USD



### Main

Range of product	9422T
Product or component type	Disconnect Switch
Disconnecter device type	Fusible disconnect switch

### Complementary

Product mounting	Flange rod variable depth
Line Rated Current	200 A
Maximum Horse Power Rating	40 Hp 200 V AC 60 Hp 230 V AC 125 Hp 460 V AC 150 Hp 575 V AC 40 Hp 250 V DC
Associated fuse rating	200 A 250/600 V
Provided equipment	6 in handle included NEMA 1/3/3R/4 enclosures sheet steel
Fuse type	R H K J

### Environment

Product certifications	CSA UL Recognized
------------------------	----------------------

### Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901120292
Nbr. of units in pkg.	1
Package weight(Lbs)	28.37 Lb(US) (12.87 kg)

Returnability	Yes
Country of origin	MX

**Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	9.00 In (22.86 cm)
Package 1 width	12.30 In (31.242 cm)
Package 1 Length	20.50 In (52.07 cm)

**Offer Sustainability**

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

**Contractual warranty**

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**