

# Product data sheet

## Characteristics

# 9422BTCF33

Operating mechanism, flange mounted, fixed depth assembly, 30A, 600V, fuseholder, switch mechanism, 6 inch handle



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 637.00 USD



### Main

Range of product	9422T
Product or component type	Disconnect Switch
Disconnect device type	Fusible disconnect switch

### Complementary

Product mounting	Bracket fixed depth
Line Rated Current	30 A
Maximum Horse Power Rating	7.5 Hp 200 V AC 7.5 Hp 230 V AC 15 Hp 460 V AC 20 Hp 575 V AC 5 Hp 250 V DC
Associated fuse rating	60 A 250 V 30 A 600 V
Provided equipment	6 in handle included
Fuse type	H K J R

### Environment

Product certifications	CSA UL Recognized
------------------------	----------------------

## Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901872306
Nbr. of units in pkg.	1
Package weight(Lbs)	23.10 Lb(US) (10.479 kg)
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.50 In (19.05 cm)
Package 1 width	11.00 In (27.94 cm)
Package 1 Length	16.50 In (41.91 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**