

# Product data sheet

## Characteristics

# 9422BTDF62

Operating mechanism, flange mounted, fixed depth assembly, 60A, 600 V, fuseholder, switch mechanism, 6 inch handle



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 737.90 USD



### Main

Range of product	9422T
Product or component type	Disconnect Switch
Disconnect device type	Fusible disconnect switch

### Complementary

Product mounting	Bracket fixed depth
Line Rated Current	60 A
Maximum Horse Power Rating	15 Hp 200 V AC 15 Hp 230 V AC 30 Hp 460 V AC 50 Hp 575 V AC 10 Hp 250 V DC
Associated fuse rating	60 A 600 V
Provided equipment	6 in handle included
Fuse type	J

### Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

### Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901162629
Nbr. of units in pkg.	1
Package weight(Lbs)	17.26 Lb(US) (7.831 kg)
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	13.00 In (33.02 cm)
Package 1 width	8.50 In (21.59 cm)
Package 1 Length	12.00 In (30.48 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**