

Product data sheet

Characteristics

9422TDF63C

Operating mechanism, flange mounted, variable depth, 60A, 600V, H, K, J, R fuseholder, cable operated switch mechanism



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 552.50 USD



Main

Range of Product	9422T
Product or Component Type	Disconnect Switch
Disconnecter device type	Fusible disconnect switch

Complementary

Product mounting	Flange cable variable depth
Line Rated Current	60 A
Maximum Horse Power Rating	15 Hp 200 V AC 15 Hp 230 V AC 30 Hp 460 V AC 50 Hp 575 V AC 10 Hp 250 V DC
Associated fuse rating	60 A 600 V
Provided equipment	Ordered separately
Fuse type	K H J R

Environment

Product Certifications	CSA UL Recognized
------------------------	----------------------

Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901865674
Nbr. of units in pkg.	1
Package weight(Lbs)	5.20 Lb(US) (2.359 kg)

Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.00 In (17.78 cm)
Package 1 width	11.00 In (27.94 cm)
Package 1 Length	16.00 In (40.64 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	-----------------------