

# Product data sheet

## Characteristics

# 9422TEF10C

Operating mechanism, flange mounted, variable depth, 100A, 600V, H, K, J, R fuseholder, cable operated switch mechanism



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 903.20 USD



### Main

Range of Product	9422T
Product or Component Type	Disconnect Switch
Disconnecter device type	Fusible disconnect switch

### Complementary

Product mounting	Flange cable variable depth
Line Rated Current	100 A
Maximum Horse Power Rating	25 Hp 200 V AC 30 Hp 230 V AC 60 Hp 460 V AC 75 Hp 575 V AC 20 Hp 250 V DC
Associated fuse rating	100 A 250/600 V
Provided equipment	Ordered separately
Fuse type	J R H K

### Environment

Product Certifications	CSA UL Recognized
------------------------	----------------------

### Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901712152
Nbr. of units in pkg.	1
Package weight(Lbs)	5.88 Lb(US) (2.67 kg)

Returnability	No
Country of origin	MX

**Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	7.00 In (17.78 cm)
Package 1 width	11.00 In (27.94 cm)
Package 1 Length	16.00 In (40.64 cm)

**Offer Sustainability**

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

**Contractual warranty**

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**