

Product data sheet

Characteristics


9422TG1

Operating mechanism, flange mounted, fixed depth, 400A, 600 V, no fuse, switch mechanism



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 3134.30 USD



Main

Range of product	9422T
Product or component type	Disconnect Switch
Disconnect device type	Non-fusible disconnect switch

Complementary

Product mounting	Flange rod variable depth
Line Rated Current	400 A
Maximum Horse Power Rating	75 Hp 200 V AC 125 Hp 230 V AC 250 Hp 460 V AC 350 Hp 575 V AC 50 Hp 250 V DC
Provided equipment	Ordered separately

Environment

Product certifications	CSA UL Recognized
------------------------	----------------------

Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901728009
Nbr. of units in pkg.	1
Package weight(Lbs)	45.09 Lb(US) (20.454 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	12.50 In (31.75 cm)
Package 1 width	17.50 In (44.45 cm)
Package 1 Length	29.50 In (74.93 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**