

Product data sheet

Characteristics

9999SX6

Auxiliary contact, Type S, 1 NO contact, external, field convertible



Product availability: Stock - Normally stocked in distribution facility

Price*: 86.00 USD



Main

Range of product	Type S
Product or component type	Auxiliary Contact Module
Product destination	Contacteur starter

Complementary

NEMA size	0 3 6 7 4 5 1 00 2
Auxiliary contact composition	1 NO
[Ue] rated operational voltage	<= 600 V AC 50/60 Hz
Rated breaking capacity	6 A 120 V AC inductive control circuit UL 508 3 A 240 V AC inductive control circuit UL 508 1.2 A 600 V AC inductive control circuit UL 508 1.5 A 480 V AC inductive control circuit UL 508 10 A <= 600 V AC resistive control circuit UL 508
Height	1.5 In (38.10 mm)
Width	3 In (76.20 mm)
Depth	4.5 In (114.30 mm)
Net Weight	0.20 Lb(US) (0.09 kg)

Environment

Product certifications	CSA UL Listed UL Recognized
------------------------	-----------------------------------

Ordering and shipping details

Category	21761 - 9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	00785901733300
Nbr. of units in pkg.	1
Package weight(Lbs)	3.20 Oz (90.719 g)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.50 In (3.81 cm)
Package 1 width	3.10 In (7.874 cm)
Package 1 Length	4.60 In (11.684 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	21
Package 2 Weight	12.40 Lb(US) (5.625 kg)
Package 2 Height	8.00 In (20.32 cm)
Package 2 width	11.30 In (28.702 cm)
Package 2 Length	14.20 In (36.068 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**