

Product data sheet

Characteristics

9999TC10

Disconnect mechanism, flange mounted,
disconnect switch auxiliary contact kit, 15A, 1
pole, SPDT



Product availability: Stock - Normally stocked in distribution facility

Price*: 120.00 USD



Main

Range	Square D
Product or Component Type	Interlock
Device Application	Control

Complementary

Range compatibility	Disconnect Switch
[Ie] rated operational current	15 A120 V AC 50/60 Hz 15 A240 V AC 50/60 Hz 15 A480 V AC 50/60 Hz 15 A600 V AC 50/60 Hz
Maximum Height	4.16 In (105.66 mm)
Maximum Depth	1.44 In (36.58 mm)
Net Weight	0.51 Lb(US) (0.23 kg)


Ordering and shipping details

Category	21761 - 9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	00785901858478
Nbr. of units in pkg.	1
Package weight(Lbs)	8.16 Oz (231.332 g)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.20 ln (8.128 cm)
Package 1 width	4.20 ln (10.668 cm)
Package 1 Length	6.70 ln (17.018 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	----------------