



Product availability: Stock - Normally stocked in distribution facility

Price\*: 602.00 USD



## Main

Range	PowerPact
Product name	PowerPact B
Device short name	BK 020
Product or Component Type	Circuit breaker
Device Application	Distribution

## Complementary

Line Rated Current	20 A
Poles description	1P
Control Type	Toggle
Breaking capacity code	K
Breaking capacity	100 KA 208Y/120 V AC 50/60 Hz UL 489 100 KA 240 V AC 50/60 Hz UL 489 65 KA 480Y/277 V AC 50/60 Hz UL 489 65 KA 600Y/347 V AC 50/60 Hz UL 489
Network Frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 KV IEC 60947-2
Trip unit technology	Thermal-magnetic
Continuous current rating	80 %
[Ui] rated insulation voltage	800 V IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category A
Mechanical durability	20000 Cycles IEC 947-1 Annex K ed 5.2
Electrical durability	10000 Cycles IEC 947-1 Annex K ed 5.2 440 V In
Connection pitch	1.06 In (27 mm)
AWG gauge	AWG 14...AWG 2/0 aluminium/copper
Local signalling	Presence of auxiliary contacts flag green)
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load

Mounting Height	1.50 In (38.1 mm)
Tightening torque	31.86...38.94 Lbf.In (3.6...4.4 N.m) 0.00...0.01 in <sup>2</sup> (2.5...6 mm <sup>2</sup> ) (AWG 14...AWG 10) 44.25...54.87 Lbf.In (5...6.2 N.m) 0.02...0.11 in <sup>2</sup> (10...70 mm <sup>2</sup> ) (AWG 8...AWG 2/0)
Color	Grey (RAL 7016)
9 mm pitches	3
Maximum Height	5.39 In (137 mm)
Maximum Width	1.06 In (27 mm)
Maximum Depth	3.50 In (89 mm)
Net Weight	1.41 Lb(US) (0.6375 kg)
Quantity per Set	Set of 1
Phase connection	C

## Environment

Standards	EN/IEC 60947-2 UL 489 CSA C22.2 No 5 GB 14048.2 NEMA AB1 NMX J-266 EN/IEC 60947-5-1
Product certifications	UL IEC CCC EAC CSA NOM
IP degree of protection	Front cover IP40 IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Pollution degree	3 IEC 60947-1
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-58...185 °F (-50...85 °C)
Operating altitude	< 6561.68 ft (2000 m) without derating 5000 m with derating



## Ordering and shipping details

Category	01135 - BJA/BKA I-LINE BREAKER
Discount Schedule	DE2
GTIN	00785901067818
Nbr. of units in pkg.	1
Package weight(Lbs)	25.76 Oz (730.284 g)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.50 In (3.81 cm)
Package 1 width	7.75 In (19.685 cm)
Package 1 Length	11.63 In (29.528 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes
Halogen content performance	Halogen free product

Product Life Status :	<b>Commercialised</b>
-----------------------	-----------------------