



Product availability: Stock - Normally stocked in distribution facility



Main

Range of Product	Modicon X80
Product or Component Type	Power supply module
Product Compatibility	All backplane
Function Available	Uptime duration Temperature sensing Remaining lifetime Redundancy information Redundancy test
Primary voltage	125 V
Supply circuit type	DC
Secondary power	18 W 3.3 V DC 32...140 °F (0...60 °C) I/O module logic power supply 40 W 24 V DC 32...140 °F (0...60 °C) I/O module power supply and processor if 3.3 V not loaded

Complementary

Primary voltage limit	100...150 V
Input current	600 MA 125 V
Inrush current	60 A 125 V
I ² t on activation	2.5 A ² .S 125 V
It on activation	0.09 A.S 125 V
Protection type	Internal fuse not accessible primary circuit Overload protection secondary circuit Overvoltage protection secondary circuit Short-circuit protection secondary circuit
Current at secondary voltage	1.67 A 24 V DC I/O module power supply and processor 5 A 3.3 V DC I/O module logic power supply
Maximum power dissipation in W	8.5 W
Status LED	Presence of voltages (OK) 1 LED Green Redundancy OK 1 LED Green Power supply status 1 LED Green)
Control Type	RESET push-button cold restart
Electrical connection	1 connector 2 alarm relay 1 connector 5 line supply, protective earth

Insulation resistance	>= 100 MΩ primary/ground ≥ 100 MΩ primary/secondary
Net Weight	1.34 Lb(US) (0.61 kg)

Environment

Immunity to microbreaks	1 Ms
Dielectric strength	1500 V primary/secondary I/O module logic power supply 1500 V primary/secondary I/O module power supply and processor 2300 V primary/secondary sensor power supply 1500 V primary/ground
IP Degree of Protection	IP20
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Environmental characteristic	3C3 EN/IEC 60721-3-3 3C4 EN/IEC 60721-3-3
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Ambient air temperature for operation	32...140 °F (0...60 °C)
Relative humidity	10...95 % without condensation

Ordering and shipping details

Category	18160 - MODICON M340
Discount Schedule	PC34
GTIN	3606481179098
Nbr. of units in pkg.	1
Package weight(Lbs)	21.87 Oz (620 g)
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.54 In (9 cm)
Package 1 width	7.09 In (18 cm)
Package 1 Length	10.04 In (25.5 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Weight	9.30 Lb(US) (4.22 kg)
Package 2 Height	11.81 In (30 cm)
Package 2 width	11.81 In (30 cm)
Package 2 Length	15.75 In (40 cm)
Unit Type of Package 3	P06
Number of Units in Package 3	48
Package 3 Weight	95.24 Lb(US) (43.2 kg)
Package 3 Height	27.56 In (70 cm)
Package 3 width	23.62 In (60 cm)
Package 3 Length	31.50 In (80 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Product Life Status : **Commercialised**