

Product data sheet

Characteristics

DU221RBUP

Safety switch, general duty, non fusible, 30A, 2 poles, 3 hp, 240 VAC, NEMA 3R, bolt-on provision



Product availability: Stock - Normally stocked in distribution facility

Price*: 118.00 USD



Main

Product or component type	Single Throw Safety Switch
Series name	General duty
Device application	Residential
Disconnecter device type	Non-fusible disconnect switch
Device composition	None
Phase	3 phase
Number of poles	2
Line Rated Current	30 A
[Ue] rated operational voltage	240 V AC
NEMA degree of protection	NEMA 3R
Maximum Horse Power Rating	3 Hp 240 V at AC 60 Hz for 1 phase conforming to NEC 430.52

Complementary

Device mounting	Surface
Electrical connection	Lugs
Wiring configuration	2 wires
AWG gauge	AWG 14...AWG 6 copper AWG 12...AWG 6 aluminium
Tightening torque	30 Lbf.In (3.39 N.m) 0.00...0.02 in ² (2.08...13.3 mm ²) (AWG 14...AWG 6)
Depth	3.75 in (95.25 mm)
Width	7.75 in (196.85 mm)
Height	9.63 in (244.60 mm)
Net weight	3.97 Lb(US) (1.8 kg)

Environment

Product certifications	UL listed file E2875
------------------------	----------------------

Ordering and shipping details

Category	00106 - D & DU SW,NEMA3R, 30-200A
Discount Schedule	DE1A
GTIN	00785901665625
Nbr. of units in pkg.	1
Package weight(Lbs)	4.86 Lb(US) (2.20 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	5.70 In (14.478 cm)
Package 1 width	7.90 In (20.066 cm)
Package 1 Length	10.60 In (26.924 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**