

Product data sheet

Characteristics

GS2AH420

External rotary handle, TeSys GS, red handle, front mounting, 2 positions I-O, NEMA 4-4X, for GS 30A Compact UL



Product availability: Stock - Normally stocked in distribution facility

Price*: 70.00 USD



Main

Range of product	TeSys
Range	TeSys
Device short name	GS2AH
Product or component type	Rotary handle
Range compatibility	TeSys GS GS1D fuse-switch disconnect
Type of operating handle	External frontal
Handle colour	Red
Handle front plate colour	Yellow

Complementary

Marking	O-I
Rotary handle padlocking	With
Line Rated Current	30 A
Standards	CSA UL
Net weight	0.44 Lb(US) (0.2 kg)

Environment

NEMA degree of protection	NEMA 4/4X
---------------------------	-----------

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	03389119411868
Nbr. of units in pkg.	1
Package weight(Lbs)	7.83 Oz (222 g)

Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.44 In (6.2 cm)
Package 1 width	2.95 In (7.5 cm)
Package 1 Length	4.72 In (12 cm)
Unit Type of Package 2	BAG
Number of Units in Package 2	1
Package 2 Weight	7.80 Oz (221 g)
Package 2 Height	2.36 In (6 cm)
Package 2 width	5.91 In (15 cm)
Package 2 Length	7.09 In (18 cm)
Unit Type of Package 3	S01
Number of Units in Package 3	3
Package 3 Weight	30.65 Oz (869 g)
Package 3 Height	5.91 In (15 cm)
Package 3 width	5.91 In (15 cm)
Package 3 Length	15.75 In (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: S-tyrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**