

Product data sheet

Characteristics

H225XJGAA

Safety switch, heavy duty, molded case, 225A, 3 poles, 150 hp, 600 VAC/250 VDC, NEMA 7/9



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 6701.00 USD

Main

Product or component type	Single Throw Safety Switch
Series name	Heavy duty
Device application	Heavy application
Disconnecter device type	Fusible disconnect
Device composition	None
Phase	3 phase
Number of poles	2
Line Rated Current	400 A
[Ue] rated operational voltage	250 V DC 240 V AC
NEMA degree of protection	NEMA 7/9 Cast Aluminium
Maximum Horse Power Rating	60 Hp 240 V at AC 50-60 Hz for 3 phase 125 Hp 480 V at AC 50-60 Hz for 3 phase 150 Hp 600 V at AC 50-60 Hz for 3 phase

Complementary

Device mounting	Surface
AWG gauge	AWG 1/0...750 kcmil copper or aluminium
Tightening torque	550 Lbf.In (62.14 N.m) (AWG 1/0...750 kcmil)
Depth	7.7 In (195.58 mm)
Width	10.93 In (277.62 mm)
Height	22.7 In (576.58 mm)
Net weight	42.99 Lb(US) (19.5 kg)

Environment

Product certifications	UL listed file E2875
------------------------	----------------------

Ordering and shipping details

Category	00160 - DE1 MISC
Discount Schedule	DE1
GTIN	00785901588344
Nbr. of units in pkg.	1
Package weight(Lbs)	44.2 Lb(US) (20.05 kg)
Returnability	No
Country of origin	MX

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. *Prices are indicative. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**