

# Product data sheet

## Characteristics

### H227NAWK

Safety switch, heavy duty, fusible, 800A, 2 poles, 50 hp, 240 VAC/250 VDC, NEMA 12, neutral factory installed



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 12338.00 USD

#### Main

Product or component type	Single Throw Safety Switch
Series name	Heavy duty
Device application	Heavy application
Disconnecter device type	Fusible disconnect
Device composition	Neutral (factory installed)
Phase	3 phase
Number of poles	2
Line Rated Current	800 A
[Ue] rated operational voltage	250 V DC 240 V AC
NEMA degree of protection	NEMA 3R/12 galvannealed steel
Maximum Horse Power Rating	50 Hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 50 Hp 250 V at DC

#### Complementary

Short-circuit current	200 KA maximum L
Fuse type	L
Device mounting	Surface
Electrical connection	Lugs
Wiring configuration	3-wire
AWG gauge	AWG 3/0...750 kcmil copper or aluminium
Tightening torque	375 Lbf.In (42.37 N.m) 0.13...0.59 in <sup>2</sup> (85.01...380 mm <sup>2</sup> ) (AWG 3/0...750 kcmil)
Depth	17.75 In (450.85 mm)
Width	36.62 In (930.15 mm)
Height	69.13 In (1755.90 mm)
Net weight	371.04 Lb(US) (168.3 kg)

#### Environment

Product certifications	UL listed file E2875
------------------------	----------------------

#### Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901638834
Nbr. of units in pkg.	1
Package weight(Lbs)	361 Lb(US) (163.75 kg)
Returnability	No
Country of origin	MX

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. \*Prices are indicative. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**