

# H228AWK

Safety switch, heavy duty, fusible, 1200A, 2 poles,  
50 hp, 240 VAC/250 VDC, NEMA 12



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 15815.00 USD



## Main

Product or component type	Single Throw Safety Switch
Series name	Heavy duty
Device application	Heavy application
Disconnecter device type	Fusible disconnect
Device composition	None
Phase	3 phase
Number of poles	2
Line Rated Current	1200 A
[Ue] rated operational voltage	250 V DC 240 V AC
NEMA degree of protection	NEMA 3R/12 galvanized steel
Maximum Horse Power Rating	50 Hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 50 Hp 250 V at DC

## Complementary

Short-circuit current	200 KA maximum L
Fuse type	L
Device mounting	Surface
Electrical connection	Lugs
Wiring configuration	2-wire
AWG gauge	AWG 3/0...750 kcmil copper or aluminium
Tightening torque	375 Lbf.In (42.37 N.m) 0.13...0.59 in <sup>2</sup> (85.01...380 mm <sup>2</sup> ) (AWG 3/0...750 kcmil)
Depth	17.75 In (450.85 mm)
Width	36.62 In (930.15 mm)
Height	69.13 In (1755.90 mm)
Net weight	358.91 Lb(US) (162.8 kg)

## Environment

Product certifications	UL listed file E2875
------------------------	----------------------

### Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901637066
Nbr. of units in pkg.	1
Package weight(Lbs)	364 Lb(US) (165.11 kg)
Returnability	No
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	----------------