

Product data sheet

Characteristics

H361AWCVW

Safety switch, heavy duty, fusible, 30A, 600 VAC/VDC, 3 poles, 20 hp, NEMA 12K, crouse hinds arktite, viewing window



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 2393.00 USD



Main

Product or component type	Receptacle Switch
Product destination	Plug APJ3485 Crouse-Hinds Arktite
Disconnecter device type	Fusible disconnect switch
Phase	3 phase
Number of poles	3
Line Rated Current	30 A
[Ue] rated operational voltage	600 V AC 250 V DC
NEMA degree of protection	NEMA 12K
Maximum Horse Power Rating	5 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 Hp 250 V at DC conforming to NEC 240.6

Complementary

Short-circuit current	10 KA H or K 200 KA R or J
Fuse type	H or K R or J
Device mounting	Surface
Electrical connection	Receptacle
Wiring configuration	4-wire Without neutral
AWG gauge	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	45 Lbf.In (5.08 N.m) (AWG 6) 40 Lbf.In (4.52 N.m) (AWG 8) 35 Lbf.In (3.95 N.m) (AWG 14...AWG 10)
Depth	7 In (177.80 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. *Prices are indicative. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Width	10.5 In (266.70 mm)
Height	16.5 In (419.10 mm)
Net weight	30.86 Lb(US) (14 kg)

Environment

Product certifications	UL Listed
------------------------	-----------

Ordering and shipping details

Category	00116 - H&HU SW,4&6P,N12,30-200A
Discount Schedule	DE1
GTIN	00785901824244
Nbr. of units in pkg.	1
Package weight(Lbs)	23.00 Lb(US) (10.433 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	31.44 In (79.849 cm)
Package 1 width	7.37 In (18.732 cm)
Package 1 Length	13.44 In (34.129 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**