

Product data sheet

Characteristics

H361DSWA

Safety switch, heavy duty, fusible, 30A, 600 VAC/
VDC, 3 poles, 20 hp, NEMA Type 4, 4X, 5, 304
steel, appleton receptacle



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 4401.00 USD

Main

Product or component type	Receptacle Switch
Product destination	Plug ACP3034BC Appleton Powertite
Disconnecter device type	Fusible disconnect switch
Phase	3 phase
Number of poles	3
Line Rated Current	30 A
[Ue] rated operational voltage	600 V AC 250 V DC
NEMA degree of protection	NEMA 4/4X/5 stainless steel 304
Maximum Horse Power Rating	5 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 Hp 250 V at DC conforming to NEC 240.6

Complementary

Short-circuit current	10 KA H or K 200 KA R or J
Fuse type	H or K R or J
Device mounting	Surface
Electrical connection	Receptacle
Wiring configuration	4-wire
AWG gauge	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	45 Lbf.In (5.08 N.m) (AWG 6) 40 Lbf.In (4.52 N.m) (AWG 8) 35 Lbf.In (3.95 N.m) (AWG 14...AWG 10)
Depth	5.11 In (129.79 mm)
Width	10.81 In (274.57 mm)
Height	16.87 In (428.50 mm)
Net weight	30.86 Lb(US) (14 kg)

Environment

Product certifications	UL Listed
------------------------	-----------

Ordering and shipping details

Category	00124 - H&HU SW,W/APPLETON RECPT - WA
Discount Schedule	DE1
GTIN	03606481243836
Nbr. of units in pkg.	1
Package weight(Lbs)	13 Lb(US) (5.90 kg)

Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	31.44 In (79.849 cm)
Package 1 width	7.37 In (18.732 cm)
Package 1 Length	13.44 In (34.129 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**