

# Product data sheet

## Characteristics

# H362AWCVW

Safety switch, heavy duty, fusible, 60A, 600 VAC/VDC, 3 poles, 50 hp, NEMA 12K, crouse hinds arktite, viewing window



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 2885.00 USD



## Main

Product or component type	Receptacle Switch
Product destination	Plug APJ6485 Crouse-Hinds Arktite
Disconnecter device type	Fusible disconnect switch
Phase	3 phase
Number of poles	3
Line Rated Current	60 A
[Ue] rated operational voltage	600 V AC 250 V DC
NEMA degree of protection	NEMA 12K
Maximum Horse Power Rating	15 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 30 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 15 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 50 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 10 Hp 250 V at DC conforming to NEC 240.6

## Complementary

Short-circuit current	10 KA H or K 100 KA R, J or T 200 KA R, J or T
Fuse type	H or K R, J or T R, J or T
Device mounting	Surface
Electrical connection	Receptacle
Wiring configuration	Without neutral 4-wire
AWG gauge	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) (AWG 8) 35 Lbf.In (3.95 N.m) (AWG 14...AWG 10)

Depth	7 In (177.80 mm)
Width	10.5 In (266.70 mm)
Height	16.5 In (419.10 mm)
Net weight	26.46 Lb(US) (12 kg)

## Environment

Product certifications	UL Listed
------------------------	-----------

## Ordering and shipping details

Category	00117 - H&HU SW,VIEW WINDOW(VW)
Discount Schedule	DE1
GTIN	00785901208983
Nbr. of units in pkg.	1
Package weight(Lbs)	24 Lb(US) (10.89 kg)
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**