

# Product data sheet

## Characteristics

# H664AWK

Safety switch, heavy duty, fusible, 200A, 4 poles, 150 hp, 600 VAC/DC, NEMA 12



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 12222.00 USD



### Main

Product or component type	Single Throw Safety Switch
Series name	Heavy duty
Device application	Heavy application
Disconnecter device type	Fusible disconnect
Device composition	None
Phase	3 phase
Number of poles	6
Line Rated Current	200 A
[Ue] rated operational voltage	600 V AC
NEMA degree of protection	NEMA 3R/12 galvannealed steel
Maximum Horse Power Rating	30 Hp 240 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 50 Hp 240 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 25 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 60 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 Hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 50 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 125 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 Hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 60 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 150 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 40 Hp 250 V at DC 50 Hp 600 V at DC

### Complementary

Short-circuit current	10 KA H or K 200 KA R, J or L
Fuse type	H or K R, J or L
Device mounting	Surface
Electrical connection	Lugs
Wiring configuration	6-wire
AWG gauge	AWG 6...250 kcmil copper or aluminium

Tightening torque	275 Lbf.In (31.07 N.m) 0.02...0.20 in <sup>2</sup> (13.3...127 mm <sup>2</sup> ) (AWG 6...250 kcmil)
Depth	8.75 In (222.25 mm)
Width	24.88 In (631.95 mm)
Height	29 In (736.60 mm)
Net weight	88.01 Lb(US) (39.92 kg)

## Environment

Product certifications	UL listed file E2875
------------------------	----------------------

## Ordering and shipping details

Category	00116 - H&HU SW,4&6P,N12,30-200A
Discount Schedule	DE1
GTIN	00785901396758
Nbr. of units in pkg.	1
Package weight(Lbs)	88.00 Lb(US) (39.916 kg)
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.13 In (18.11 cm)
Package 1 width	16.50 In (41.91 cm)
Package 1 Length	26.00 In (66.04 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**