

# HDL26015C

Circuit breaker, PowerPacT H, thermal magnetic, unit mount, 15A, 2 pole, 14kA, 600 VAC, 100% rated



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 1566.00 USD



## Main

|                           |                 |
|---------------------------|-----------------|
| Range                     | PowerPact       |
| Product name              | PowerPact H     |
| Product or component type | Circuit breaker |
| Device application        | Distribution    |

## Complementary

|  |   |
|--|---|
| Line Rated Current                     | 15 A  |
| Poles description                      | 2P  |
| Protected poles description            | 2t  |
| Control type                           | Toggle  |
| Breaking capacity code                 | D   |
| Breaking capacity                      | 25 KA 240 V AC 50/60 Hz UL 489<br>18 KA 480 V AC 50/60 Hz<br>14 KA 600 V AC 50/60 Hz<br>20 KA 250 V DC  |
| [Ue] rated operational voltage         | 690 V AC 50/60 Hz IEC 60947-3   |
| Network frequency                      | 50/60 Hz  |
| [Ics] rated service breaking capacity  | 25 KA 220/240 V AC 50/60 Hz IEC 60947-2<br>18 KA 380/440/415 V AC 50/60 Hz IEC 60947-2<br>14 KA 500/525 V AC 50/60 Hz IEC 60947-2<br>20 KA 250 V DC IEC 60947-2<br>20 KA 500 V DC IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 8 KV IEC 60947-2  |
| Trip unit technology                   | Thermal-magnetic  |
| Magnetic tripping current              | 750 A   |
| Magnetic hold current                  | 350 A   |
| Continuous current rating              | 100 %   |
| [Ui] rated insulation voltage          | 750 V IEC 60947-2   |
| Suitability for isolation              | Yes conforming to IEC 60947-2   |

|                         |  |
|-------------------------|--|
| Utilisation category    | Category A   |
| AWG gauge               | AWG 14...AWG 3/0 aluminium/copper terminal   |
| Local signalling        | Switched off (OFF) 1 trip indicator green)   |
| Mounting mode           | Unit mount lug)  |
| Mounting support        | Lug  |
| Electrical connection   | Lugs line<br>Lugs load   |
| Terminal identifier     | AL150HD  |
| Tightening torque       | 44.25 Lbf.In (5 N.m) 0.00...0.01 in <sup>2</sup> (2.5...6 mm <sup>2</sup> ) (AWG 14...AWG 10)<br>123.91 Lbf.In (14 N.m) 0.02...0.15 in <sup>2</sup> (10...95 mm <sup>2</sup> ) (AWG 8...AWG 3/0) |
| Number of slots         | 2 auxiliary switch OF plug-in)<br>1 alarm switch SD plug-in)<br>1 overcurrent trip switch SDE plug-in)<br>1 voltage release MN or MX plug-in)  |
| Wire stripping length   | 0.63 In (16 mm)  |
| Color                   | Black  |
| Height                  | 6.42 In (163 mm)   |
| Width                   | 4.09 In (104 mm)   |
| Depth                   | 3.39 In (86 mm)  |
| Net weight              | 4.85 Lb(US) (2.2 kg)   |
| Quantity per set        | 1  |
| Communication interface | Modbus<br>Ethernet   |

## Environment

|                                       |  |
|---------------------------------------|--|
| Quality labels                        | CE   |
| Standards                             | UL<br>CSA<br>NEMA<br>NOM-003-SCFI-2000<br>IEC 60947-2          |
| Product certifications                | UL<br>CSA<br>NOM   |
| IP degree of protection               | Front cover IP40 IEC 60529                                     |
| Pollution degree                      | 3 IEC 60947-1  |
| Ambient air temperature for operation | 28...158 °F (-2...70 °C)                                       |
| Ambient air temperature for storage   | -58...185 °F (-50...85 °C)                                     |
| Operating altitude                    | < 6561.68 ft (2000 m) without derating<br>5000 m with derating |

## Ordering and shipping details

|                       |                                      |
|-----------------------|--------------------------------------|
| Category              | 01110 - HD,JD UNIT MT BREAKER/SWITCH |
| Discount Schedule     | DE2                                  |
| GTIN                  | 00785901671237                       |
| Nbr. of units in pkg. | 1                                    |
| Package weight(Lbs)   | 3.00 Lb(US) (1.361 kg)               |
| Returnability         | Yes                                  |
| Country of origin     | US                                   |

## Packing Units

|                        |                     |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE                 |
| Package 1 Height       | 5.13 In (13.018 cm) |
| Package 1 width        | 7.25 In (18.415 cm) |
| Package 1 Length       | 8.44 In (21.433 cm) |

### Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| California proposition 65  | WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        | <a href="#">End Of Life Information</a>  |
| PVC free                   | Yes  |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

|                       |                       |
|-----------------------|-----------------------|
| Product Life Status : | <b>Commercialised</b> |
|-----------------------|-----------------------|