

# HGL36000S15

## AUTOMATIC MOLDED CASE SWITCH 600V 150A



Product availability: Stock - Normally stocked in distribution facility

Price\*: 1799.00 USD



### Main

Product or component type	Automatic switch
Range of product	PowerPact H
Trip unit technology	Magnetic

### Complementary

Line Rated Current	150 A
[Ue] rated operational voltage	600 V AC 250 V DC
Mounting mode	Unit mount
Poles description	3P
Short-circuit withstand	65 KA 240 V UL 489 35 KA 480 V UL 489 18 KA 600 V UL 489
Breaking capacity code	G
Electrical connection	Lugs line Lugs load
AWG gauge	AWG 14...AWG 3/0 aluminium/copper)
Terminal identifier	AL150HD
Magnetic tripping current	2250 A
Height	6.4 In (162.56 mm)
Width	2.12 In (53.85 mm)
Depth	4.36 In (110.74 mm)
Tightening torque	44.25 Lbf.In (5 N.m) 0.00...0.15 in <sup>2</sup> (2.5...95 mm <sup>2</sup> ) (AWG 14...AWG 3/0)

### Environment

Product certifications	CE IEC NMX UL Listed CCC CSA
------------------------	---------------------------------------------

## Ordering and shipping details

Category	01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901433958
Nbr. of units in pkg.	1
Package weight(Lbs)	4.13 Lb(US) (1.875 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.60 In (14.224 cm)
Package 1 width	7.50 In (19.05 cm)
Package 1 Length	8.80 In (22.352 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**