

Product data sheet

Characteristics

HLL36125

Circuit breaker, PowerPacT H, thermal magnetic, unit mount, 125A, 3 pole, 50 kA, 600 VAC, 80% rated



Product availability: Stock - Normally stocked in distribution facility

Price*: 6749.00 USD



Main

Range of product	PowerPact H
Product or component type	Circuit breaker

Complementary

Line Rated Current	125 A
Poles description	3P
Breaking capacity code	L
Mounting mode	Unit mount
Magnetic hold current	900 A
Magnetic tripping current	1700 A
Electrical connection	Lugs load Lugs line
Tightening torque	44.25 Lbf.In (5 N.m) 0.00...0.15 in ² (2.5...95 mm ²) (AWG 14...AWG 3/0)
Height	6.4 In (162.56 mm)
Width	4.12 In (104.65 mm)
Depth	4.36 In (110.74 mm)
Continuous current rating	80 %

Environment

Product certifications	UL Listed IEC CSA CE
Ambient air temperature for operation	104 °F (40 °C)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative

Ordering and shipping details

Category	01120 - HL,JL UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901953043
Nbr. of units in pkg.	1
Package weight(Lbs)	4.19 Lb(US) (1.9 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.80 In (14.732 cm)
Package 1 width	7.40 In (18.796 cm)
Package 1 Length	8.70 In (22.098 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**