

Product data sheet

Characteristics

HU362DSWAVW

Safety switch, heavy duty, non fusible, 60A, 600 VAC/VDC, 3 poles, 60 hp, NEMA Type 4, 4X, 5, appleton, window



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 4448.00 USD



Main

Product or component type	Receptacle Switch
Product destination	Plug ACP6034BC Appleton Powertite
Disconnecter device type	Non-fusible disconnect switch
Phase	3 phase
Number of poles	3
Line Rated Current	60 A
[Ue] rated operational voltage	600 V AC 250 V DC
NEMA degree of protection	NEMA 4/4X/5 stainless steel 304
Maximum Horse Power Rating	50 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 60 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 10 Hp 250 V at DC conforming to NEC 430.52

Complementary

Device mounting	Surface
Electrical connection	Receptacle
Wiring configuration	Without neutral 4-wire
AWG gauge	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) (AWG 8) 35 Lbf.In (3.95 N.m) (AWG 14...AWG 10)
Depth	5.11 In (129.79 mm)
Width	10.81 In (274.57 mm)
Height	16.87 In (428.50 mm)

Environment

Product certifications	UL Listed
------------------------	-----------

Ordering and shipping details

Category	00124 - H&HU SW,W/APPLETON RECPT - WA
Discount Schedule	DE1
GTIN	00785901351894
Nbr. of units in pkg.	1
Package weight(Lbs)	17.00 Lb(US) (7.711 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	18.69 In (47.464 cm)
Package 1 width	7.37 In (18.732 cm)
Package 1 Length	11.00 In (27.94 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**