

Product data sheet

Characteristics

HU366NR

Safety switch, heavy duty, non fusible, 600A, 3 poles, 500 hp, 600 VAC/DC, NEMA 3R, neutral factory installed



Product availability: Stock - Normally stocked in distribution facility

Price*: 8010.00 USD



Main

Product or component type	Single Throw Safety Switch
Series name	Heavy duty
Device application	Heavy application
Disconnector device type	Non-fusible disconnect
Device composition	Neutral (factory installed)
Phase	3 phase
Number of poles	3
Line Rated Current	600 A
[Ue] rated operational voltage	600 V AC/DC
NEMA degree of protection	NEMA 3R galvannealed steel
Maximum Horse Power Rating	200 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 400 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 500 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 Hp 250 V at DC conforming to NEC 430.52 50 Hp 600 V at DC

Complementary

Device mounting	Surface
Electrical connection	Lugs
Wiring configuration	4-wire (3PH + N)
AWG gauge	AWG 3/0...500 kcmil copper or aluminium
Tightening torque	375 Lbf.In (42.37 N.m) (AWG 3/0...500 kcmil)
Depth	10.13 In (257.30 mm)
Width	27.88 In (708.15 mm)
Height	50.31 In (1277.87 mm)

Environment

Product certifications	UL listed file E2875
------------------------	----------------------

Ordering and shipping details

Category	00054 - H&HU SW,NEMA3R,400-1200A
Discount Schedule	DE1
GTIN	00785901112211
Nbr. of units in pkg.	1
Package weight(Lbs)	178 Lb(US) (80.74 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.13 Ft (0.343 m)
Package 1 width	2.33 Ft (0.711 m)
Package 1 Length	4.25 Ft (1.295 m)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**