

Product data sheet

Characteristics

HU464AWKVW

Safety switch, heavy duty, non fusible, 200A, 4 poles, 150 hp, 600 VAC/DC, NEMA 12, viewing window



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 2877.00 USD

Main

Product or component type	Single Throw Safety Switch
Series name	Heavy duty
Device application	Heavy application
Disconnecter device type	Non-fusible disconnect
Device composition	None
Phase	3 phase
Number of poles	4
Line Rated Current	200 A
[Ue] rated operational voltage	600 V AC/DC
NEMA degree of protection	NEMA 3R/12
Maximum Horse Power Rating	50 Hp 240 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 60 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 Hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 125 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 Hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 150 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 40 Hp 250 V at DC 50 Hp 600 V at DC

Complementary

Device mounting	Surface
Wiring configuration	4-wire
AWG gauge	AWG 6...250 kcmil copper or aluminium
Tightening torque	275 Lbf.In (31.07 N.m) 0.02...0.20 in ² (13.3...127 mm ²) (AWG 6...250 kcmil)
Depth	8.75 in (222.25 mm)
Width	18.63 in (473.20 mm)
Height	29 in (736.60 mm)
Net weight	80.49 Lb(US) (36.51 kg)

Environment

Product certifications	UL listed file E2875
------------------------	----------------------

Ordering and shipping details

Category	00117 - H&HU SW,VIEW WINDOW(VW)
Discount Schedule	DE1
GTIN	00785901291374
Nbr. of units in pkg.	1
Package weight(Lbs)	10 Lb(US) (4.54 kg)
Returnability	Yes
Country of origin	US

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. *Prices are indicative. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**