

Product data sheet

Characteristics

HU662AWKEI

Safety switch, heavy duty, non fusible, 60A, 6 poles, 60 hp, 600 VAC/DC, NEMA 12, interlock kit



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 4337.00 USD



Main

Product or component type	Single Throw Safety Switch
Series name	Heavy duty
Device application	Heavy application
Disconnecter device type	Non-fusible disconnect
Device composition	None
Phase	3 phase
Number of poles	6
Line Rated Current	60 A
[Ue] rated operational voltage	600 V AC/DC
NEMA degree of protection	NEMA 3R/12
Maximum Horse Power Rating	20 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 60 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52

Complementary

Device mounting	Surface
Wiring configuration	6-wire
AWG gauge	AWG 14...AWG 3 copper AWG 12...AWG 3 aluminium
Tightening torque	50 Lbf.In (5.65 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 50 Lbf.In (5.65 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) (AWG 14...AWG 10)
Depth	6.8 In (172.72 mm)
Width	16.13 In (409.70 mm)
Height	20.5 In (520.70 mm)

Environment

Product certifications	UL listed file E2875
------------------------	----------------------

Ordering and shipping details

Category	00160 - DE1 MISC
Discount Schedule	DE1
GTIN	00785901939863
Nbr. of units in pkg.	1
Package weight(Lbs)	10.00 Lb(US) (4.536 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.10 In (18.034 cm)
Package 1 width	16.80 In (42.672 cm)
Package 1 Length	25.70 In (65.278 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**