

Product data sheet

Characteristics

HU664AWK

Safety switch, heavy duty, non fusible, 200A, 6 poles, 150 hp, 600 VAC/DC, NEMA 12



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 10538.00 USD



Main

Product or component type	Single Throw Safety Switch
Series name	Heavy duty
Device application	Heavy application
Disconnecter device type	Non-fusible disconnect
Device composition	None
Phase	3 phase
Number of poles	6
Line Rated Current	200 A
[Ue] rated operational voltage	600 V AC
NEMA degree of protection	NEMA 3R/12 galvannealed steel
Maximum Horse Power Rating	60 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 125 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 150 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52

Complementary

Device mounting	Surface
Electrical connection	Lugs
Wiring configuration	6-wire
AWG gauge	AWG 6...250 kcmil copper or aluminium
Tightening torque	275 Lbf.In (31.07 N.m) 0.02...0.20 in ² (13.3...127 mm ²) (AWG 6...250 kcmil)
Depth	8.75 in (222.25 mm)
Width	24.88 in (631.95 mm)
Height	29 in (736.60 mm)
Net weight	82.50 Lb(US) (37.42 kg)

Environment

Product certifications	UL listed file E2875
------------------------	----------------------

Ordering and shipping details

Category	00116 - H&HU SW,4&6P,N12,30-200A
Discount Schedule	DE1
GTIN	00785901396765
Nbr. of units in pkg.	1
Package weight(Lbs)	72.00 Lb(US) (32.659 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.40 In (18.796 cm)
Package 1 width	17.10 In (43.434 cm)
Package 1 Length	26.30 In (66.802 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**