

Product data sheet

Characteristics

JDL26200

Circuit breaker, PowerPacT J, unit mount, thermal-magnetic, 200A, 2 pole 14 kA, 600 VAC



Product availability: Stock - Normally stocked in distribution facility

Price*: 2175.00 USD



Main

Product or component type	Circuit breaker
---------------------------	-----------------

Complementary

Line Rated Current	200 A
Poles description	2P
Breaking capacity code	D
Magnetic tripping current	2000 A
Magnetic hold current	1000 A
Continuous current rating	80 %
Electrical connection	Lugs load Lugs line
Tightening torque	230.12 Lbf.In (26 N.m) 0.15...0.29 in ² (95...185 mm ²) (AWG 3/0...350 kcmil)
Height	7.52 In (191.01 mm)
Width	4.12 In (104.65 mm)
Depth	5 In (127.00 mm)

Ordering and shipping details

Category	01110 - HD,JD UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901955801
Nbr. of units in pkg.	1
Package weight(Lbs)	4.52 Lb(US) (2.05 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.71 In (14.5 cm)
Package 1 width	7.40 In (18.8 cm)
Package 1 Length	8.90 In (22.6 cm)


Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions



Product Life Status : **Commercialised**