

Product data sheet

Characteristics

JDL36150T

Circuit breaker, PowerPacT J, unit mount, thermal-magnetic, 150A, 3 pole 14 kA, 600 VAC



Price*: 2730.00 USD



Main

Product or component type	Circuit breaker
---------------------------	-----------------

Complementary

Poles description	3P
Breaking capacity code	D
Installed device	Trip unit field installable
Magnetic hold current	750 A
Magnetic tripping current	1500 A
Electrical connection	Lugs load Lugs line
Tightening torque	230.12 Lbf.In (26 N.m) 0.04...0.15 in ² (25...95 mm ²) (AWG 4...AWG 4/0)
Height	7.52 In (191.01 mm)
Width	4.12 In (104.65 mm)
Depth	5 In (127.00 mm)
Continuous current rating	80 %

Ordering and shipping details

Category	01110-HD,JD UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901697855
Package weight(Lbs)	4.50 Lb(US) (2.041 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**