

Product data sheet

Characteristics

JGL26000S25

POWERPACT AUTOMATIC MOULDED CASE SWITCH 600V 250 A J-Frame



Price*: 1827.00 USD

Main

| | |
|---------------------------|------------------|
| Product or component type | Automatic switch |
| Range of product | PowerPact J |
| Trip unit technology | Magnetic |
| Circuit breaker type | J-frame |

Complementary

| | |
|--------------------------------|--|
| Line Rated Current | 250 A |
| [Ue] rated operational voltage | 600 V AC |
| Mounting mode | Unit mount |
| Poles description | 2P |
| Short-circuit withstand | 65 KA 240 V UL 489 35 KA 480 V UL 489 18 KA 600 V UL 489 |
| Breaking capacity code | G |
| Electrical connection | Lugs line Lugs load |
| AWG gauge | AWG 3/0...350 kcmil aluminium/copper) |
| Terminal identifier | AL250JD |
| Magnetic tripping current | 3125 A |
| Height | 7.52 In (191.01 mm) |
| Width | 2.74 In (69.60 mm) |
| Depth | 5 In (127.00 mm) |
| Tightening torque | 230.12 Lbf.In (26 N.m) 0.15...0.29 in ² (95...185 mm ²) (AWG 3/0...350 kcmil) |

Environment

| | |
|------------------------|-------------------------|
| Product certifications | IEC UL Listed CSA |
|------------------------|-------------------------|

Ordering and shipping details

| | |
|---------------------|--|
| Category | 01115-HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH |
| Discount Schedule | DE2 |
| GTIN | 00785901683247 |
| Package weight(Lbs) | 5.00 Lb(US) (2.268 kg) |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------|---------------------|
| Package 1 Height | 5.50 In (13.970 cm) |
| Package 1 width | 7.50 In (19.050 cm) |
| Package 1 Length | 8.50 In (21.590 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**