

# Product data sheet

## Characteristics

# JJA261751

Circuit breaker, PowerPacT J, I-Line, thermal magnetic, 175A, 2 pole, 25 kA, 600 VAC, phase AB



Price\*: 4904.00 USD

### Main

Product or component type	Circuit breaker
---------------------------	-----------------

### Complementary

Poles description	2P
Breaking capacity code	J
Magnetic hold current	875 A
Magnetic tripping current	1750 A
Electrical connection	I-Line connection line Lugs load
Tightening torque	230.12 Lbf.In (26 N.m) 0.04...0.15 in <sup>2</sup> (25...95 mm <sup>2</sup> ) (AWG 4...AWG 4/0)
Phase connection	AB
Height	11.48 In (291.59 mm)
Width	4.48 In (113.79 mm)
Depth	5.87 In (149.10 mm)
Continuous current rating	80 %

### Ordering and shipping details

Category	01117-HG, HJ, JG, JJ I-LINE BREAKER/SWITC
Discount Schedule	DE2
GTIN	00785901415312
Nbr. of units in pkg.	1
Package weight(Lbs)	4.50 Lb(US) (2.041 kg)
Returnability	Yes
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.38 In (13.653 cm)
Package 1 width	8.13 In (20.638 cm)
Package 1 Length	14.63 In (37.148 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

**Contractual warranty**

Warranty	18 months
----------	-----------

Product Life Status :	<b>Commercialised</b>
-----------------------	-----------------------