

Product data sheet

Characteristics

JJA36250U33X

Circuit breaker, PowerPacT J, I-Line, Micrologic
3.2S, 250A, 3 pole, 25 kA, 600 VAC, phase ABC



Price*: 6249.00 USD



Main

Product or component type	Circuit breaker
---------------------------	-----------------

Complementary

Poles description	3P
Breaking capacity code	J
Magnetic hold current	1250 A
Magnetic tripping current	2500 A
Electrical connection	I-Line connection line Lugs load
Tightening torque	230.12 Lbf.In (26 N.m) 0.15...0.29 in ² (95...185 mm ²) (AWG 3/0...350 kcmil)
Phase connection	ABC
Height	11.48 In (291.59 mm)
Width	4.48 In (113.79 mm)
Depth	5.87 In (149.10 mm)
Continuous current rating	80 %

Ordering and shipping details

Category	01104-H/J ELEC TRIP I-LINE BREAKER / SW
Discount Schedule	DE2
GTIN	00785901606314
Nbr. of units in pkg.	1
Package weight(Lbs)	7.11 Lb(US) (3.225 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.38 In (13.653 cm)
Package 1 width	8.13 In (20.638 cm)
Package 1 Length	14.63 In (37.148 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**