

# Product data sheet

## Characteristics

# JLA36150

Circuit breaker, PowerPacT J, I-Line, thermal magnetic, 150A, 3 pole, 50 kA, 600 VAC, phase ABC



Product availability: Stock - Normally stocked in distribution facility

Price\*: 7299.00 USD



### Main

Product or component type	Circuit breaker
---------------------------	-----------------

### Complementary

Poles description	3P
Breaking capacity code	L
Magnetic hold current	750 A
Magnetic tripping current	1500 A
Electrical connection	I-Line connection line Lugs load
Tightening torque	230.12 Lbf.In (26 N.m) 0.04...0.15 in <sup>2</sup> (25...95 mm <sup>2</sup> ) (AWG 4...AWG 4/0)
Phase connection	ABC
Height	11.48 In (291.59 mm)
Width	4.48 In (113.79 mm)
Depth	5.87 In (149.10 mm)
Continuous current rating	80 %

### Ordering and shipping details

Category	01122 - HL, JL I-LINE BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901700722
Nbr. of units in pkg.	1
Package weight(Lbs)	6.07 Lb(US) (2.75 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Package 1 Height	6.00 In (15.240 cm)
Package 1 width	8.50 In (21.590 cm)
Package 1 Length	14.90 In (37.846 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**