

# LC2D40AG7

TeSys D reversing contactor - 3P(3 NO) - AC-3 -  
≤ 440 V 40 A - 120 V AC coil

Product availability: Stock - Normally stocked in distribution facility

Price\*: 565.00 USD



## Main

Commercial Status	Commercialised
Range	TeSys
Product name	TeSys D
Product or component type	Reversing contactor
Device short name	LC2D
Contactor application	Motor control Resistive load
Utilisation category	AC-1 AC-3
Device presentation	Preassembled with reversing power busbar
Poles description	3P
Pole contact composition	3 NO
System Voltage	≤ 300 V DC power circuit ≤ 690 V AC 25...400 Hz power circuit
[Ie] rated operational current	60 A (≤ 140 °F (60 °C)) at ≤ 440 V AC AC-1 power circuit 40 A (≤ 140 °F (60 °C)) at ≤ 440 V AC AC-3 power circuit
Motor power kW	30 kW at 660...690 V AC 50/60 Hz 22 kW at 500 V AC 50/60 Hz 22 kW at 415...440 V AC 50/60 Hz 11 kW at 220...230 V AC 50/60 Hz 18.5 kW at 380...400 V AC 50/60 Hz
Motor power hp	30 hp at 460/480 V AC 50/60 Hz 3 phases motors 3 hp at 115 V AC 50/60 Hz 1 phase motors 10 hp at 200/208 V AC 50/60 Hz 3 phases motors 30 hp at 575/600 V AC 50/60 Hz 3 phases motors 10 hp at 230/240 V AC 50/60 Hz 3 phases motors 5 hp at 230/240 V AC 50/60 Hz 1 phase motors
Control circuit type	AC 50/60 Hz
Control circuit voltage	120 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 1 NC
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
Overvoltage category	III
[Ith] conventional free air thermal current	60 A at ≤ 140 °F (60 °C) power circuit 10 A at ≤ 140 °F (60 °C) signalling circuit
Irms rated making capacity	800 A at 440 V power circuit conforming to IEC 60947 250 A DC signalling circuit conforming to IEC 60947-5-1 140 A AC signalling circuit conforming to IEC 60947-5-1
Rated breaking capacity	800 A at 440 V power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	720 A ≤ 104 °F (40 °C) 1 s power circuit 320 A ≤ 104 °F (40 °C) 10 s power circuit 165 A ≤ 104 °F (40 °C) 1 min power circuit 72 A ≤ 104 °F (40 °C) 10 min power circuit 140 A 100 ms signalling circuit 120 A 500 ms signalling circuit 100 A 1 s signalling circuit

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. \*Prices are indicative

Associated fuse rating	80 A gG at ≤ 690 V coordination type 2 power circuit 80 A gG at ≤ 690 V coordination type 1 power circuit 10 A gG signalling circuit conforming to IEC 60947-5-1
Average impedance	At 50 Hz - Ith 60 A for power circuit
[Ui] rated insulation voltage	600 V signalling circuit certifications UL 600 V signalling circuit certifications CSA 690 V signalling circuit conforming to IEC 60947-1 600 V power circuit certifications UL 600 V power circuit certifications CSA 690 V power circuit conforming to IEC 60947-4-1
Electrical durability	1.4 Mcycles 60 A AC-1 at Ue ≤ 440 V 1.5 Mcycles 40 A AC-3 at Ue ≤ 440 V
Power dissipation per pole	5.4 W AC-1 2.4 W AC-3
Protective cover	With
Interlocking type	Mechanical
Mounting support	Plate Rail
Standards	EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 CSA C22.2 No 14
Product certifications	CCC CSA GOST UL
Connections - terminals	Power circuit: EverLink BTR screw connectors 2 cable(s) 0...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) - cable stiffness: solid - without cable end Power circuit: EverLink BTR screw connectors 1 cable(s) 0...0.05 in <sup>2</sup> (1...35 mm <sup>2</sup> ) - cable stiffness: solid - without cable end Power circuit: EverLink BTR screw connectors 2 cable(s) 0...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Power circuit: EverLink BTR screw connectors 1 cable(s) 0...0.05 in <sup>2</sup> (1...35 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Power circuit: EverLink BTR screw connectors 2 cable(s) 0...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end Power circuit: EverLink BTR screw connectors 1 cable(s) 0...0.05 in <sup>2</sup> (1...35 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 2 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid - without cable end Control circuit: screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid - without cable end Control circuit: screw clamp terminals 2 cable(s) 0...0 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 2 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end
Tightening torque	Power circuit: 70.8 lbf.in (8 N.m) - on EverLink BTR screw connectors - cable 0.04...0.05 in <sup>2</sup> (25...35 mm <sup>2</sup> ) hexagonal 0.16 in (4 mm) Power circuit: 44.25 lbf.in (5 N.m) - on EverLink BTR screw connectors - cable ≤ 0.04 in <sup>2</sup> (25 mm <sup>2</sup> ) hexagonal 0.16 in (4 mm) Control circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 15.04 lbf.in (1.7 N.m) - on screw clamp terminals - with screwdriver flat Ø 6 mm

Operating time	12...26 ms closing 4...19 ms opening
Safety reliability level	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
Mechanical durability	6 Mcycles
Operating rate	3600 cyc/h at <= 140 °F (60 °C)

## Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.85...1.1 Uc at 140 °F (60 °C) operational 60 Hz 0.8...1.1 Uc at 140 °F (60 °C) operational 50 Hz 0.3...0.6 Uc at 140 °F (60 °C) drop-out 50/60 Hz
Inrush power in VA	160 VA at 68 °F (20 °C) (cos $\phi$ 0.75) 50 Hz 140 VA at 68 °F (20 °C) (cos $\phi$ 0.75) 60 Hz
Hold-in power consumption in VA	15 VA at 68 °F (20 °C) (cos $\phi$ 0.3) 50 Hz 13 VA at 68 °F (20 °C) (cos $\phi$ 0.3) 60 Hz
Heat dissipation	4...5 W at 50/60 Hz
Auxiliary contacts type	Type mirror contact (1 NC) conforming to IEC 60947-4-1 Type mechanically linked (1 NO + 1 NC) conforming to IEC 60947-5-1
Signalling circuit frequency	25...400 Hz
Minimum switching current	5 mA signalling circuit
Non-overlap time	1.5 ms on energisation (between NC and NO contact) 1.5 ms on de-energisation (between NC and NO contact)
Insulation resistance	> 10 MOhm signalling circuit

## Environment

IP degree of protection	IP2x front face conforming to IEC 60529
Protective treatment	TH conforming to IEC 60068-2-30
Pollution degree	3
Ambient air temperature for operation	23...140 °F (-5...60 °C)
Ambient air temperature for storage	-76...176 °F (-60...80 °C)
Permissible ambient air temperature around the device	-40...158 °F (-40...70 °C) at Uc
Operating altitude	9842.52 ft (3000 m) without derating in temperature
Fire resistance	1562 °F (850 °C) conforming to IEC 60695-2-1
Flame retardance	V1 conforming to UL 94
Mechanical robustness	Shocks contactor closed 15 Gn for 11 ms Shocks contactor open 10 Gn for 11 ms Vibrations contactor closed 4 Gn, 5...300 Hz Vibrations contactor open 2 Gn, 5...300 Hz
Height	4.8 in (122 mm)
Width	4.69 in (119 mm)
Depth	4.72 in (120 mm)
Product weight	4.12 lb(US) (1.87 kg)

## Ordering and shipping details

Category	22346 - CTR,D-LINE,OPEN,REVERSING-NEW
Discount Schedule	I12
GTIN	00785901562535
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	FR

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---