



### Main

Range	TeSys
Product name	TeSys LK
Product or component type	Disconnect Switch
Disconnect device type	Non-fusible disconnect switch
Suitability for isolation	Yes

### Complementary

Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	63 A 400 V AC AC-22A IEC 63 A 400 V AC AC-23A IEC 63 A 690 V AC AC-22A IEC 63 A 690 V AC AC-23A IEC 60 A CSA 60 A UL
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ui] rated insulation voltage	750 V
Control type	Rotary handle
Type of operating handle	External right side External frontal
Mounting support	Plate
[Uimp] rated impulse withstand voltage	8 KV IEC
Rated power in W	30 KW 400 V 40 KW 500 V 55 KW 690 V
Rated power in hp	20 Hp 240 V 56 A AC 40 Hp 480 V 53 A AC 50 Hp 600 V 52 A AC
[Icw] rated short-time withstand current	17.6 KA
Mechanical durability	10000 Cycles
Electrical durability	6000 Cycles
Connections - terminals	Lugs-ring terminals 1 0.01 in <sup>2</sup> (4 mm <sup>2</sup> )
Height	4.92 In (125 mm)

Width	3.13 In (79.5 mm)
Depth	2.52 In (64 mm)

## Environment

Standards	UL98 CSA C22.2 No 4 IEC 60947-3
Product certifications	UL CSA CE

## Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	00785901333470
Nbr. of units in pkg.	1
Package weight(Lbs)	1 Lb(US) (0.45 kg)
Returnability	No
Country of origin	CN

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.27 In (8.3 cm)
Package 1 width	3.54 In (9 cm)
Package 1 Length	6.30 In (16 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Weight	25.91 Lb(US) (11.752 kg)
Package 2 Height	11.81 In (30 cm)
Package 2 width	11.81 In (30 cm)
Package 2 Length	15.75 In (40 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: S-tyrene, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**