

Product data sheet

Characteristics

LK4MU3N

Disconnect Switch, TeSys LK, nonfusible, 200A, 600 V, HP rated, 3 pole, rotary handle, up to 200kA SCCR

Product availability: Stock - Normally stocked in distribution facility

Price*: 1010.00 USD



Main

Range	TeSys
Product name	TeSys LK
Product or Component Type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

Complementary

Poles description	3P
Network type	AC DC
Network Frequency	50/60 Hz
[Ie] rated operational current	200 A 400 V AC AC-22A IEC 200 A 400 V AC AC-23A IEC 200 A 690 V AC AC-22A IEC 200 A 690 V AC AC-23A IEC 200 A CSA 200 A UL
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	750 V
Control Type	Rotary handle
Type of operating handle	External frontal External right side
Mounting Support	Plate
[Uimp] rated impulse withstand voltage	8 KV IEC
Rated power in W	100 KW 400 V 140 KW 500 V 185 KW 690 V
Rated power in hp	75 Hp 240 V 92 A AC 150 Hp 480 V 187 A AC 200 Hp 600 V 192 A AC 15 Hp 125 V 112 A DC 15 Hp 250 V 56 A DC
[Icw] rated short-time withstand current	32 KA

Mechanical durability	8000 Cycles
Electrical durability	6000 Cycles
Connections - terminals	Lugs-ring terminals 1 0.02 in ² (16 mm ²)
Maximum Height	6.30 in (160 mm)
Maximum Width	7.09 in (180 mm)
Maximum Depth	3.74 in (95 mm)
Net Weight	5.03 Lb(US) (2.28 kg)

Environment

Standards	IEC 60947-3 CSA C22.2 No 4 UL98
Product Certifications	UL CSA CE

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	03606480510458
Nbr. of units in pkg.	1
Package weight(Lbs)	4.99 Lb(US) (2.264 kg)
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.69 in (17 cm)
Package 1 width	11.02 in (28 cm)
Package 1 Length	11.02 in (28 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Weight	22.73 Lb(US) (10.308 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: S-tyrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty 18 months

Product Life Status : Commercialised