

Product data sheet

Characteristics

LV426821

pre-wired MN undervoltage release, ComPact NSXm, rated voltage 24 VDC, 24 VAC 50/60Hz



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 716.00 USD



Main

Device short name	MN
Product or Component Type	Voltage release
Device Application	Control
Range compatibility	PowerPact B ComPact NSXm
Voltage release type	Undervoltage release
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC

Complementary

Threshold tripping voltage	0.35...0.7 x Un opening 0.85 x Un closing
Mounting Mode	Clip-on
Response time	< 50 ms
Auxiliary connection terminal	Pre-wired 0.00...0.00 in ² (0...0.8 mm ²) AWG 18)stranded copper
Wire stripping length	0.31 In (8 mm)
Length	3.28 Ft (1 m)

Ordering and shipping details

Category	01136 - PP-B FRAME ACCESSORIES
Discount Schedule	DE2
GTIN	03606485412917
Nbr. of units in pkg.	1
Package weight(Lbs)	1 Lb(US) (0.45 kg)
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.34 In (3.4 cm)
Package 1 width	2.40 In (6.1 cm)
Package 1 Length	3.27 In (8.3 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Product Life Status : **Commercialised**