

LV426950

standard auxiliary contact, ComPact NSXm,
circuit breaker status OF/SD, 1 changeover
contact type



Product availability: Stock - Normally stocked in distribution facility

Price*: 257.00 USD



Main

Product or Component Type	Auxiliary contact
Device short name	SD OF
Device Application	Breaker status monitoring
Range compatibility	PowerPact B ComPact NSXm
Signal contacts composition	1 NO/NC

Complementary

Fault type	Overload Short-circuit
Local signalling	For open/close ON/OFF indication for relay trip indicator trip indicator
Auxiliary contacts type	Standard
Mounting Mode	Clip-on
[I _{th}] conventional free air thermal current	5 A

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative

[I _e] rated operational current	AC-12 5 A 24 V AC 50/60 Hz AC-12 5 A 48 V AC 50/60 Hz AC-12 5 A 110...127 V AC 50/60 Hz AC-12 5 A 220/240 V AC 50/60 Hz AC-12 5 A 380/440 V AC 50/60 Hz AC-12 5 A 660/690 V AC 50/60 Hz AC-15 5 A 24 V AC 50/60 Hz AC-15 5 A 48 V AC 50/60 Hz AC-15 4 A 110...127 V AC 50/60 Hz AC-15 3 A 220/240 V AC 50/60 Hz AC-15 2.5 A 380/440 V AC 50/60 Hz AC-15 0.1 A 660/690 V AC 50/60 Hz DC-12 5 A 24 V DC DC-12 2.5 A 48 V DC DC-12 0.6 A 110 V DC DC-12 0.3 A 250 V DC DC-13 2.5 A 24 V DC DC-13 1.2 A 48 V DC DC-13 0.35 A 110 V DC DC-13 0.05 A 250 V DC DC-14 1 A 24 V DC DC-14 0.2 A 48 V DC DC-14 0.05 A 110 V DC DC-14 0.03 A 250 V DC
Minimum load	2 MA 17 V DC
Auxiliary connection terminal	Spring
Wire stripping length	0.31 In (8 mm) front

Ordering and shipping details

Category	01136 - PP-B FRAME ACCESSORIES
Discount Schedule	DE2
GTIN	03606485444215
Nbr. of units in pkg.	1
Package weight(Lbs)	0.88 Oz (25 g)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.47 In (1.2 cm)
Package 1 width	2.95 In (7.5 cm)
Package 1 Length	4.13 In (10.5 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	9.17 Oz (260 g)
Package 2 Height	5.51 In (14 cm)
Package 2 width	1.97 In (5 cm)
Package 2 Length	9.84 In (25 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	220
Package 3 Weight	13.62 Lb(US) (6.176 kg)
Package 3 Height	11.81 In (30 cm)
Package 3 width	11.81 In (30 cm)
Package 3 Length	15.75 In (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Product Life Status : **Commercialised**