

Product data sheet

Characteristics

M9U21216

Multi9 - C60H-DC - MCB - 2P - 16 A - C Curve -
500 V DC - 10 kA

Product availability: Stock - Normally stocked in distribution facility

Price*: 392.00 USD



Main

Range	Multi 9
Product name	Multi 9 C60H-DC
Product or Component Type	Miniature circuit-breaker
Device short name	C60H-DC
Device Application	Distribution
Poles description	2P
Number of protected poles	2
Line Rated Current	16 A 77 °F (25 °C) EN/IEC 60947-2
Network type	DC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	20 KA Icu 220 V DC EN/IEC 60947-2 10 KA Icu 440 V DC EN/IEC 60947-2 6 KA Icu 500 V DC EN/IEC 60947-2 5 KA AIR 12...500 V DC UL 1077 20 KA Icu 220 V DC GB 14048.2 10 KA Icu 440 V DC GB 14048.2 6 KA Icu 500 V DC GB 14048.2
Utilisation category	Category A EN/IEC 60947-2
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Standards	EN/IEC 60947-2 GB 14048.2 UL 1077
Product certifications	IEC CCC UR

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative

Complementary

[Ue] rated operational voltage	220 V DC 440 V DC 500 V DC
Magnetic tripping limit	7...10 x I _n DC
[Ics] rated service breaking capacity	7.5 KA 75 % EN/IEC 60947-2 - 440 V DC 4.5 KA 75 % EN/IEC 60947-2 - 500 V DC 15 KA 75 % EN/IEC 60947-2 - 220 V DC 7.5 KA 75 % GB 14048.2 - 440 V DC 4.5 KA 75 % GB 14048.2 - 500 V DC 15 KA 75 % GB 14048.2 - 220 V DC
[Ui] rated insulation voltage	500 V DC EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	6 KV EN/IEC 60947-2
Contact position indicator	Yes
Control Type	Toggle
Local signalling	ON/OFF indication
Mounting Mode	Clip-on
Mounting Support	DIN rail
9 mm pitches	4
Maximum Height	3.19 In (81 mm)
Maximum Width	1.42 In (36 mm)
Maximum Depth	2.87 In (73 mm)
Net Weight	0.28 Lb(US) (0.128 kg)
Color	Gray
Mechanical durability	20000 Cycles
Electrical durability	3000 Cycles 250 V DC L/R = 2 ms 6000 Cycles 250 V DC
Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminal top or bottom) 0.00...0.04 in ² (1...25 m- m ²) AWG 18...AWG 4) - rigid stranded Tunnel type terminal top or bottom) 0.00...0.02 in ² (1...16 m- m ²) AWG 18...AWG 6) - flexible Tunnel type terminal top or bottom) 0.00...0.02 in ² (1...16 m- m ²) AWG 18...AWG 6) - flexible with ferrule Tunnel type terminal top or bottom) - 2 0.00...0.02 in ² (1...10 m- m ²) AWG 18...AWG 8) - rigid stranded Tunnel type terminal top or bottom) - 2 0.00...0.02 in ² (1...10 m- m ²) AWG 18...AWG 8) - flexible Tunnel type terminal top or bottom) - 2 0.00...0.02 in ² (1...10 m- m ²) AWG 18...AWG 8) - flexible with ferrule Tunnel type terminal top or bottom) - 3 0.00 in ² (1 mm ²) AWG 18) - flexible stranded
Wire stripping length	0.55 In (14 mm) top or bottom
Tightening torque	22.13 Lbf.In (2.5 N.m) top or bottom
Earth-leakage protection	Without

Environment

Heat dissipation	5 W 440 V - 16 A
IP degree of protection	IP20 IEC 60529 IP40 modular enclosure) IEC 60529
Pollution degree	3 EN/IEC 60947-2
Tropicalisation	2 IEC 60068-2 2 GB 14048.2
Relative humidity	95 % 131 °F (55 °C)
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	00948 - M9 GEN 2 CB UL1077 / IEC
Discount Schedule	DE2
GTIN	03606480741807
Nbr. of units in pkg.	1
Package weight(Lbs)	7.94 Oz (225 g)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.35 In (8.5 cm)
Package 1 width	1.42 In (3.6 cm)
Package 1 Length	2.83 In (7.2 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Product Life Status : **Commercialised**