

Product data sheet

Characteristics

MG26925

Multi9 accy, aux switch, 20 A, 120/240 V, 1 pole,
10 kA, DIN rail



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 60.00 USD



Main

Range	Multi 9
Line Rated Current	20 A

Complementary

[Ue] rated operational voltage	120/240 V 277 V 65 V
Poles description	1P
Breaking capacity	10 KA 5 KA
Mounting support	DIN rail

Environment

Product certifications	IEC UL listed
------------------------	------------------

Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901892175
Nbr. of units in pkg.	12
Package weight(Lbs)	0.09 Lb(US) (0.04 kg)
Returnability	No
Country of origin	BE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.80 In (2.032 cm)
Package 1 width	3.10 In (7.874 cm)
Package 1 Length	3.40 In (8.636 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commerc. announced**

MG26925 may be replaced by any of the following products:



M9A26924

Multi9 - OC contact - 1 OF - 240/415 V AC - 24/130 V DC

Qty 1

Substitution date: |