

Product data sheet

Characteristics

NSYPIN86

Internal door for Spacial WM encl. H800xW600 steel, RAL7035.Adjustable in depth



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 175.84 USD



Main

Range	Spacial
Accessory / separate part category	Enclosure accessory
Product or component type	Door
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting location	Step slide Front side
Range compatibility	Spacial CRN Spacial S3D Spacial S3X
Device composition	1 door 4 fixing brackets 2 mounting uprights

Complementary

Material	Door sheet steel
Color	All faces Gray RAL 7035)
Surface finish	Polyester powder
Lock type	Lock 3 mm double bar
Number of locks	1
Adjustment	Pitch 25 mm (on step slides)
Door type	Internal plain
Door opening side	Reversible
Maximum load	30 kg/m ²
Height	Nominal 31.50 in (800 mm)
Width	Nominal 23.62 in (600 mm)
Net Weight	13.67 Lb(US) (6.2 kg)

Ordering and shipping details

Category	80036 - ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	03606480168536
Nbr. of units in pkg.	1
Package weight(Lbs)	14.14 Lb(US) (6.412 kg)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.97 In (5 cm)
Package 1 width	21.85 In (55.5 cm)
Package 1 Length	30.12 In (76.5 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**