

# Product data sheet

## Characteristics

# NSYPLA1053G

Floor standing enclosure polyester vers.PLA  
completely sealed 1000x500x320 IP65



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 633.11 USD



### Main

Range	Thalassa
Product name	Thalassa PLA
Device Application	Multi-purpose
Product or Component Type	Suitable enclosure
Device short name	PLA
Enclosure nominal height	39.37 In (1000 mm)
Enclosure nominal width	19.69 In (500 mm)
Enclosure nominal depth	12.60 In (320 mm)
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part

### Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Plain front
Number of doors	1
Door opening side	Reversible 120 °)
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Front Rear
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Color	Gray RAL 7035)
Standards	UL 508 A IEC 62208

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. \*Prices are indicative

NEMA Degree of Protection	NEMA 13 NEMA 12 NEMA 3S NEMA 2 NEMA 1 NEMA 5 NEMA 3X NEMA 3 NEMA 3R
Product Certifications	Veritas DNV Marine UL/CUL listed
Electrical Insulation Class	Class II

## Environment

IP degree of protection	IP65 IEC 60529 completely sealed)
IK degree of protection	IK10 conforming to IEC 62262 (plain door)
Fire resistance	1760 °F (960 °C) IEC 62208
Ambient Air Temperature for Storage	-31...194 °F (-35...90 °C)

## Ordering and shipping details

Category	80034 - ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	03606480774430
Nbr. of units in pkg.	1
Package weight(Lbs)	47.40 Lb(US) (21.5 kg)
Returnability	No
Country of origin	ES

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	14.96 In (38 cm)
Package 1 width	20.87 In (53 cm)
Package 1 Length	40.16 In (102 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Product Life Status : **Commercialised**