

Product data sheet

Characteristics

NSYPLAT15124G

Floor standing encl. polyester vers.PLAT open top
w/ canopy 1500x1250x420 IP44



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1860.44 USD



Main

Range	Thalassa
Product name	Thalassa PLA
Device Application	Multi-purpose
Product or Component Type	Suitable enclosure
Device short name	PLAT
Enclosure nominal height	59.06 In (1500 mm)
Enclosure nominal width	49.21 In (1250 mm)
Enclosure nominal depth	16.54 In (420 mm)
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 2 door 2 rear panel 1 canopy

Complementary

Body type	Open top and sealed bottom part assembled with side parts
Door type	Plain front
Number of doors	2
Door opening side	Right and left 120 °)
Lock type	4 points lock, handle with 5 mm double bar insert
Accessibility for operation	Rear Top Front
Removable parts	Door by hinges Rear panel by fixing element Canopy by fixing element
Material	Polyester reinforced with fibreglass
Color	Grey (RAL 7035)
Standards	IEC 62208

Product Certifications	Veritas
Electrical Insulation Class	Class II

Environment

IP degree of protection	IP44 IEC 60529 with ventilated canopy)
IK degree of protection	IK10 conforming to IEC 62262 (plain door)
Fire resistance	1760 °F (960 °C) IEC 62208
Ambient Air Temperature for Storage	-31...194 °F (-35...90 °C)

Ordering and shipping details

Category	80034 - ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	03606480775345
Nbr. of units in pkg.	1
Package weight(Lbs)	204.30 Lb(US) (92.668 kg)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	59.84 In (152 cm)
Package 1 width	50.39 In (128 cm)
Package 1 Length	18.90 In (48 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**